

IBM Cloud Pak for Business Automation

Demos and Labs 2023

Orchestrating scripts in IBM RPA

V 2.0

Vinícius Dutra

v.dutra@ibm.com

Aldo Justiniano

aldo.justiniano@ibm.com

Marco Crepaldi

marco.crepaldi@ibm.com

Raul Mariano

raul.mariano@ibm.com

Pooja Luthra

pooja.luthra@ibm.com

NOTICES

This information was developed for products and services offered in the USA.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive, MD-NC119
Armonk, NY 10504-1785
United States of America

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

TRADEMARKS

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the web at "Copyright and trademark information" at www.ibm.com/legal/copytrade.shtml.

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

Cell Broadband Engine is a trademark of Sony Computer Entertainment, Inc. in the United States, other countries, or both and is used under license therefrom.

Intel, Intel logo, Intel Inside, Intel Inside logo, Intel Centrino, Intel Centrino logo, Celeron, Intel Xeon, Intel SpeedStep, Itanium, and Pentium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

IT Infrastructure Library is a Registered Trade Mark of AXELOS Limited.

ITIL is a Registered Trade Mark of AXELOS Limited.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

Linear Tape-Open, LTO, the LTO Logo, Ultrium, and the Ultrium logo are trademarks of HP, IBM Corp. and Quantum in

the U.S. and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

© Copyright International Business Machines Corporation 2020.

This document may not be reproduced in whole or in part without the prior written permission of IBM.

US Government Users Restricted Rights - Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Table of Contents

1	<i>Introduction.....</i>	6
2	<i>Process Overview</i>	7
3	<i>Pre-requisites.....</i>	7
3.1	References.....	8
4	<i>Accessing the Environment.....</i>	9
4.1	Reserve Environment.....	9
5	<i>Build it yourself – Step-by-step instructions.</i>	13
5.1	Architecture Overview	13
5.2	Exercise 1: Create Queues	14
5.2.1	Open Control Center	14
5.2.2	Enter username.....	14
5.2.3	Enter Tenant and Password	15
5.2.4	Open the Queues menu.....	15
5.2.5	Creating the customer queue	16
5.2.6	Create customer-queue.	16
5.2.7	Check the message.....	17
5.2.8	Creating the Service Queue	17
5.2.9	Check the queues.....	18
5.3	Exercise 2: Add commands to queue data.....	19
5.3.1	Open IBM RPA Studio.....	19
5.3.2	Inform the user.	19
5.3.3	Inform Tenant name and Password.....	20
5.3.4	Changing <i>script_01_getData.wal</i>	21
5.3.5	Changing <i>script_02_clientManagement.wal</i>	26
5.3.6	Changing <i>script_03_servicesManagement.wal</i>	33
5.4	Exercise 3: Create process and configure the steps.....	36
5.4.1	Return Control Center and access Workflows menu.....	36
5.4.2	Create Process.....	36
5.4.3	Create Process: General.....	37
5.4.5	Create Process: SLA Configuration	38
5.4.6	Create Process: Steps (1/4)	39
5.4.7	Create Process: Steps (2/4)	40
5.4.8	Create Process: Steps (3/4)	41
5.4.9	Create Process: Steps (4/4)	42
5.4.10	Create Process: Variables (1/3)	43
5.4.11	Create Process: Variables (2/3)	44
5.4.12	Create Process: Variables (3/3)	45
5.5	Exercise 4: Execute bot and see results.	46
5.5.1	Run Script <i>_getData.WAL</i>	46
5.5.2	See results of the process	47

1 Introduction

IBM RPA provides a comprehensive set of Robotic Process Automation (RPA) features:

- **Unattended bots**
Use an RPA-driven digital workforce to automate repetitive tasks without human intervention.
- **Attended bots**
Remote Desktop Automation (RDA) enables a human workforce to augment work using bots to perform repetitive tasks on demand.
- **Orchestrating Scripts**
Combine message queues with the orchestrator technology in your IBM RPA Control Center environment to orchestrate scripts.
- **Workflows in IBM RPA**
Combine BPMN files or create your own workflows in IBM RPA Studio and integrate them into scripts that implement the workflow process in IBM RPA.
- **Optical Character Recognition (OCR)**
Process documents by extracting structured data from unstructured content.
- **Dashboards**
Gain business insights into business operations.

With IBM RPA, IBM can provide customers with additional benefits:


- **Faster time to value**
Speed and simplicity of purchasing and deploying through easier licensing.
- **A comprehensive platform to automate all types of use cases**
Tighter integrations between RPA and the rest of IBM business automation platform.
- **Automate business and IT processes**
Expand the IBM business automation mission to IT use cases.
- **Operationalize AI**
Fulfill IBM's vision of operationalizing AI in every aspect of the business.

You can explore the [Documentation](#) to understand more details about IBM RPA.

2 Process Overview

The objective of this lab exercise is to demonstrate in practice how to use IBM RPA Orchestrator. The orchestration process leverages message queues capability of serving messages of multiple customers. It can consume messages from the message queue with the guarantee that each bot will always process independent and exclusive messages.

In this lab, we will automate the customer and service registration process, and it will be divided into three steps:



3 Pre-requisites

For this lab, you need to reserve an **IBM Robotic Process Automation** environment from IBM Technology Zone (see chapter 4). All the pre-requisites have been pre-installed/configured in the lab template. The information below is just for information purposes.

IBM Products:

- IBM Robotic Process Automation v23.0.x.

Custom Solutions/Code:

- The important files to run this lab are in [C:\CP4AutoDemo\Lab 3 - Orchestrating Scripts in IBM RPA](#)
 - *data.csv*: Spreadsheet with customer data and services that will be processed.
 - *script_01_getData.wal*: Script responsible for obtaining data from the csv spreadsheet.
 - *script_02_clientManagement.wal*: Script responsible for registering the customer in the Customer Management application.
 - *script_03_servicesManagement.wal*: Script responsible for registering the service in the Services Management application.
- A Java swing application simulating the backend, third-party system for the Client Management System.
- A web application simulating the backend, third-party Services Management System for managing the services a client has signed up to.

3.1 References

1. [IBM Robotic Process Automation Documentation](#)
2. [IBM Robotic Process Automation Command Documentation](#)
3. [IBM Robotic Process Automation Orchestrating Scripts](#)


4 Accessing the Environment

If you have already reserved a lab environment from IBM Technology Zone, please go to [Chapter 5](#) directly.


4.1 Reserve Environment

To get started with this lab, please follow the below steps to reserve an environment:


1. Click [here](#) to open IBM Technology Zone Reservation portal. You need to use your IBMID to login to the portal.



2. Click **Environments** on the left panel, and then reserve the last environment on click the blue button.



3. Select **Reserve for now**, then click **Submit**.




4. On the reservation page, make the appropriate selections as below. Once done, click **Submit**.

Purpose: Select Practice/Self-Education.

Purpose description: Enter something like **Self Education**.

End date and time: Select the end date and time that the environment will be deleted.


Preferred Geography: Select the geography where your environment will be created. To get a better network connection, select the same geography as where you are located in.



- Once you have reserved an environment, you will receive an email with a link to access the environment's management console, click on Reservation ID.



- You can access the environment using Remote Desktop (RDP) or Remote Console (Web). Our recommendation is to use Remote Console (Web) for practicality. If you prefer to use the RPD, use the Remote Desktop (RDP) link, or keep rolling the page to access the Remote Console (Web).



Public VPN Endpoint
Disabled

Router Password

Router User
admin

Router WAN IP
10.188.112.107


vCenter
itzna3-vc.na3.cloud.techzone.ibm.com

vCenter Password

vCenter Console Access
Disabled

vCenter Username
Disabled


Download and install Wireguard VPN Client
<https://wg-download.techzone.ibm.com>

Download Wireguard VPN config 

VM Remote Console

660cc5323abee4001ecaab9f-
DBA-4
Processor: 24 vCPUs
Memory: 64 GB

7. After waiting for the VM to load, open the folder BA TOOLS on the Desktop to access the IBM RPA Studio.



5 Build it yourself – Step-by-step instructions.


5.1 Architecture Overview

Keeping the focus on the proposal of this lab exercise, it will not be necessary to create the entire mapping of the systems involved in the process, the exercises are aimed at the practical use of Orchestration in IBM RPA. See [Orchestrating Scripts do IBM RPA](#) for more details on their features and usage.

Based on the process, the bot architecture will also be divided into three parts:

- **Step 1 – Get Data:**
This is the initial step of the process, where the *script_01_getData.wal* will be executed to obtain all the data for processing from the *data.csv* sheet.
- **Step 2 – Customer Management:**
The customers data obtained from the spreadsheet will be queued in the *customer-queue*, and subsequently consumed by the *script_02_clientManagement.wal*.
- **Step 3 – Services Management:**
Now that the client has been registered, the *service-queue* receives the service, which will be consumed by the *script_03_servicesManagement.wal*.


Important: The last two parts of the process (step 2 and 3) will be managed and executed by the IBM RPA Orchestrator. It is responsible for validating in each queue, the existence of any client or service to be executed, including identifying whether there is or not a machine available to run the robot.



5.2 Exercise 1: Create Queues


As previously described, the IBM RPA Orchestrator uses the concept of queues as a basis to execute the process. Therefore, the first exercise will be to create the two queues in the IBM RPA Control Center:

5.2.1 Open Control Center



#	Description
1	Start Firefox and click IBM RPA Control Center

5.2.2 Enter username.




#	Description
1	Enter the “ admin@rpa-poc.com ” as the Username
2	Click Continue

5.2.3 Enter Tenant and Password




#	Description
1	Enter the “ <i>rpa-poc</i> ” as the Tenant
2	Enter “ <i>passwOrd</i> ” (make sure to use a zero not an uppercase o) as the Password
3	Click Login

5.2.4 Open the Queues menu.



#	Description
1	Click on the Queues menu

5.2.5 Creating the customer queue




#	Description
1	Confirm that the Queue tab is selected
2	Click the Create queue button

5.2.6 Create customer-queue.

The 'Create queue' dialog box is shown. It has a title bar with a close button. Below the title bar, there are three input fields: 'Queue provider' with a dropdown menu showing 'System Queue Provider' (labeled 1), 'Name' with the text 'customer-queue' (labeled 2), and 'Description' with the text 'This queue will receive all customers who will be registered in the java app' (labeled 3). At the bottom, there are two buttons: 'Cancel' and 'Create' (labeled 4). The 'Create' button is highlighted in blue.

#	Description
1	Enter the “ <i>System Queue Provider</i> ” as the Queue provider
2	Write “ <i>customer-queue</i> ” in the Name field
3	Write a brief description about the queue
4	Click the Create button

5.2.7 Check the message.



#	Description
1	Confirm success message
2	Click the Create queue button to also add the service queue

5.2.8 Creating the Service Queue

Create queue ×

Queue provider

System Queue Provider 1 ▾

Name

service-queue 2


Description

This queue will receive service from customers who will be registered on the web portal 3

Cancel Create 4

#	Description
1	Enter the “ <i>System Queue Provider</i> ” as the Queue provider
2	Write “ <i>service-queue</i> ” in the field Name
3	Write a brief description about the queue
4	Click the Create button

5.2.9 Check the queues.




#	Description
1	Confirm success message
2	Confirm the registration of the two queues that we will use in the grid

5.3 Exercise 2: Add commands to queue data.


As presented in the [Architecture Overview](#), the entire mapping of artifacts involved in the process are already ready. So, in this exercise, we will edit each of the scripts to include only the unique commands for using the IBM RPA Orchestrator:

5.3.1 Open IBM RPA Studio




#	Description
1	Start the IBM RPA Studio by clicking the Studio icon on the Windows desktop

5.3.2 Inform the user.



#	Description
1	Write " <i>admin@rpa-poc.com</i> " in the Username field and press [enter]
2	Click the Continue button


5.3.3 Inform Tenant name and Password.



#	Description
1	Select the “ <i>rpa-poc</i> ” as the Tenant
2	Enter “ <i>passw0rd</i> ” (use a zero not a capital o)
3	Click on the Login button


5.3.4 Changing script 01 getData.wal

5.3.4.1 Open file




#	Description
1 or 2	Click on the Open button to search the script

5.3.4.2 Open script



#	Description
1	All files are in the C:\CP4AutoDemo\Lab 3 - Orchestrating Scripts in IBM RPA
2	Select the “script_01_getData.wal”
3	Click on the Open button

5.3.4.3 Connect to Queue




#	Description
1	Search " <i>queue</i> " in the toolbox
2	Let's use the command " Connect to IBM RPA Queue Server "
3	Drag the command positioning it between lines 34 and 35

5.3.4.4 Connection queue configuration




#	Description
1	Write " <i>successQueueConnect</i> " in the field Success
2	Write " <i>providerQueueConnection</i> " in the field Connection
3	Click on the Save button

5.3.4.5 Get Queue




#	Description
1	Search " <i>queue</i> " in the toolbox
2	Let's use the command " Get Queue "
3	Drag the command positioning it between lines 35 and 36

5.3.4.6 Configure the Get Queue command




#	Description
1	Click on the button and select the Connection " <i>\${providerQueueConnection}</i> "
2	Turn on the Stored Configurations (this indicates a queue that is already configured in Control Center).
3	Select the " <i>customer-queue</i> ", as mentioned previously
4	Write " <i>successToObtainTheQueue</i> " in the Success field
5	Write " <i>obtainedQueue</i> " in the Queue Obtained field
6	Click on the Save button

5.3.4.7 Customer Enqueue




#	Description
1	Search " <i>enqueue</i> " in the toolbox
2	Let's use the command " Enqueue "
3	Drag the Enqueue command into the For command (between line 39 and 40), it will add each customer to the queue

5.3.4.8 Configuration Enqueue



#	Description
1	Click on the button and select the Queue " <i>\${obtainedQueue}</i> "
2	Enable to enqueue when using a Queue provider and not a local queue
3	Click on the button and select the Inserted Item " <i>\${messageToInsert}</i> "
4	Click on the Save button


5.3.4.9 Summary and save script.



#	Description
1	For this script, it was necessary to enter the 3 commands: <ul style="list-style-type: none"> • Connect To IBM RPA Queue Server: to connect to the queue server. • Get Queue: to point to the queue that will store the items. • Enqueue: to queue each customer obtained from the CSV spreadsheet.
2	Save changes by clicking the Save button
3	WARNING! Do not run this script. Follow the steps in the guide until guidance on execution. As previously stated, this script is responsible for queuing the clients to be processed, so, for each execution, all CSV items will be queued, and this could hinder you in the final execution of the lab.


5.3.5 Changing script 02_clientManagement.wal

5.3.5.1 Open file




#	Description
1	Click on the Open button to search the script

5.3.5.2 Open script




#	Description
1	All files are in the C:\CP4AutoDemo\Lab 3 - Orchestrating Scripts in IBM RPA
2	Select the script_02_clientManagement.wal
3	Click in the Open button

5.3.5.3 Orchestration process' variables binding.



#	Description
0	Before including the other commands, it is important to present the importance of this Bind Process Variables command. For more details, visit Orchestration process' variables binding documentation
1	Double-click the Bind Process Variables command (line 41)
2	For the Orchestrator to manage the items in the queue, it is mandatory to pass some process data to be the primary key. In this case, we have already configured the <code>\$(companyCode)</code> variable. Other data can also be sent to the Orchestrator as it will be presented in the Control Center panel.
3	This command will not be changed, just click the Cancel button

5.3.5.4 Connect to Queue




#	Description
1	Search " <i>queue</i> " in the toolbox
2	Let's use the command " Connect to IBM RPA Queue Server "
3	Drag the command positioning it between lines 42 and 43

5.3.5.5 Connection queue configuration




#	Description
1	Write " <i>success</i> " in the Success field
2	Write " <i>queueConnection</i> " in the Connection field
3	Click on the Save button

5.3.5.6 Get Queue




#	Description
1	Search " <i>queue</i> " in the toolbox
2	Let's use the command " Get Queue "
3	Drag the command positioning it between lines 43 and 44

5.3.5.7 Configure the Get Queue




#	Description
1	Click on the button and select the Connection " <i>`\${queueConnection}`</i> "
2	Turn on the Stored Configurations
3	Select the " <i>customer-queue</i> ", as mentioned previously
4	Write " <i>obtainedQueue</i> " in the Queue Obtained field
5	Click on the Save button

5.3.5.8 Get Current Message from Queue




#	Description
1	Search " <i>queue</i> " in the toolbox
2	Let's use the command " Get Current Message from Queue "
3	Drag the command positioning it between lines 44 and 45

5.3.5.9 Enter the Message Structure




#	Description
1	Write " <i>itemFromQueue</i> " in the Message Structure field
2	Click on the Save button

5.3.5.11 Summary and save script.



#	Description
1	For this script, it was necessary to use these commands: <ul style="list-style-type: none"> • Bind Process Variables: To bind the primary key in the process. • Connect To IBM RPA Queue Server: to connect to the queue server. • Get Queue: to point to the queue that will store the items. • Get Current Message from Queue:
2	Save changes by clicking the Save button
3	WARNING! Do not run this script. Follow the steps in the guide until guidance on execution. This script will be executed automatically by the IBM RPA Orchestrator, so this script is not prepared to be executed in the conventional way.


5.3.5.12 Publish script.



#	Description
1	As this script will be managed by the orchestrator, it is necessary to make it public in the Control Center, then click the Publish button.
2	Keep the script name " <i>script_02_clientManagement</i> "
3	Write a brief description about the script.
4	Turn on the Set as production
5	Click " Show advanced options " to see more options
6	Configure the times (hh:mm): <ul style="list-style-type: none"> <i>Green time</i>: 00:15 <i>Yellow time</i>: 00:20 <i>Red time</i>: 00:25 Find more information in the Publishing the script documentation
7	Click on the Publish button
8	WARNING! Do not run this script. Follow the steps in the guide until guidance on execution. This script will be executed automatically by the IBM RPA Orchestrator, so this script is not prepared to be executed in the conventional way.


5.3.6 Changing script 03 servicesManagement.wal

5.3.6.1 Open file




#	Description
1	Click on the Open button to search the script

5.3.6.2 Open script




#	Description
1	All files are in the C:\CP4AutoDemo\Lab 3 - Orchestrating Scripts in IBM RPA
2	Select the “Script web.wal”
3	Click in the Open button

5.3.6.3 Orchestration process' variables binding.



#	Description
0	As in the previous script , before including the other commands, it is important to present the importance of this Bind Process Variables command. For more details, visit Orchestration process' variables binding documentation
1	Double-click the Bind Process Variables command (line 31)
2	For the Orchestrator to manage the items in the queue, it is mandatory to pass some process data to be the primary key. In this case, we have already configured the <code>\${companyCode}</code> variable. Other data can also be sent to the Orchestrator as it will be presented in the Control Center panel.
3	This command is already configured, so just click the Cancel button
5	WARNING! Do not run this script. Follow the steps in the guide until guidance on execution. This script will be executed automatically by the IBM RPA Orchestrator, so this script is not prepared to be executed in the conventional way.


5.3.6.4 Publish script.



#	Description
1	As this script will be managed by the orchestrator, it is necessary to public it in the Control Center, then click the Publish button.
2	Keep the script name " <i>script_03_servicesManagement</i> "
3	Write a brief description about the script.
4	Turn on the Set as production
5	Click " Show advanced options " to see more options
6	Configure the times (hh:mm): <ul style="list-style-type: none"> <i>Green time: 00:15</i> <i>Yellow time: 00:20</i> <i>Red time: 00:25</i> Find more information in the Publishing the script documentation
7	Click on the Publish button
8	WARNING! Do not run this script. Follow the steps in the guide until guidance on execution. This script will be executed automatically by the IBM RPA Orchestrator, so this script is not prepared to be executed in the conventional way.


5.4 Exercise 3: Create process and configure the steps.

5.4.1 Return Control Center and access Workflows menu.



#	Description
1	Click on the Workflows menu

5.4.2 Create Process



#	Description
1	Click on the Processes tab
2	Click on the Create process button

5.4.3 Create Process: General

Create process ✕

General

SLA Configuration

Steps

Variables

1

Process name

Lab3_OrchestratingScripts

Description

Select a workflow to be created with each process instances (optional)

Workflow

Workflow

Workflow Version

Select a process

What may the instances be called?

Label for Singular

2

OrchestratingScripts

Label for Plural

3

OrchestratingScripts

4

Next

#	Description
1	Write “ <i>Lab3_OrchestratingScripts</i> ” in the Process name field
2	Write “ <i>Customer</i> ” in the Label for Singular field
3	Write “ <i>Customers</i> ” in the Label for Plural field
4	Click on the Next button

5.4.5 Create Process: SLA Configuration

Create process X

General

SLA Configuration

Steps

Variables

What is the desired time interval for an instance to wait to start being processed? What is the minimal acceptable percentage of instances that is required to meet this target?

Target Waiting Time

1 00:00:05

Waiting Time Required Service Level

2 100%

What is the desired time interval for an instance to finish the whole process after starting? What is the minimal acceptable percentage of instances that is required to meet this target?

Target Handling Time

3 00:00:30

Handling Time Required Service Level

4 100%

What is the desired time interval, including waiting time, for an instance to finish the whole process? What is the minimal acceptable percentage of instances that is required to meet this target?

Target Processing Time

5 00:00:45

Processing Time Required Service Level

6 100%

Previous

7 Next

#	Description
1	Set 00:00:05 to Target Waiting Time
2	Set 100% to Waiting Time Required Service Level
3	Set 00:00:30 to Target Handling Time
4	Set 100% to Handling Time Required Service Level
5	Set 00:00:45 to Target Processing Time
6	Set 100% to Processing Time Required Service Level
7	Click on the Next button

5.4.6 Create Process: Steps (1/4)

Create process

General

SLA Configuration

Steps

Variables

Step2_CustomerManagement

Step name

1 Step2_CustomerManagement

You need to select an input queue for items to be processed and optionally a success and error queue to move items upon completion.

Input Queue

2 customer-queue

Output Queue (On Success)

3 service-queue

Priority on Success Queue

4 Normal

Output Queue (On Error)

5 Mark as error

Priority on Error Queue

6 Normal

7

Previous Next

#	Description
1	Write “ <i>Step2_CustomerManagement</i> ” in the Step name field
2	Select “ <i>customer-queue</i> ” in the Input Queue field
3	Select “ <i>service-queue</i> ” in the Output Queue field
4	Select “ <i>Normal</i> ” in the Priority on Success Queue field
5	Select “ <i>Mark as error</i> ” in the Output Queue (On Error) field
6	Select “ <i>Normal</i> ” in the Priority on Error Queue field
7	Go down

5.4.7 Create Process: Steps (2/4)

Create process

General

SLA Configuration

Steps

Variables

Mark as error

Priority on Error Queue

Normal

Which scripts will process the items in the input queue?

Script

1 script_02_clientManagement

Version

2 1 - "Script responsible for registering customer in the java app"

Where will this script run?

Computers

3 WIN-IGPQ0NALNPB

Group (optional)

Group

Previous Next

4

#	Description
1	Select “ <i>script_02_clientManagement</i> ” in the Script field
2	Select the first item (latest version of the script) in the Version field
3	Select the “ <i>WIN-IGPQ0NALNPB</i> ” in the Computers field
4	Back to the top

5.4.8 Create Process: Steps (3/4)

Create process

General

SLA Configuration

Steps

Variables

Step2_CustomerManagement

Step3_ServicesManagement

Step name

Step3_ServicesManagement

You need to select an input queue for items to be processed and optionally a success and error queue to move items upon completion

Input Queue

service-queue

Output Queue (On Success)

Mark as success

Priority on Success Queue

Normal

Output Queue (On Error)

Mark as error

Priority on Error Queue

Previous

Next

1 Add

2

3

4

5

6

7

8

#	Description
1	Click the Add button to add the last step of the process
2	To improve visualization, collapse Step2_CustomerManagement
3	Write “ <i>Step3_ServicesManagement</i> ” in the Step name field
4	Select “ <i>service-queue</i> ” in the Input Queue field
5	Select “ <i>Mark as success</i> ” in the Output Queue field
6	Select “ <i>Normal</i> ” in the Priority on Success Queue field
7	Select “ <i>Mark as error</i> ” in the Output Queue (On Error) field
8	Go down

5.4.9 Create Process: Steps (4/4)

Create process ✕

General

SLA Configuration

Steps

Variables

1

Priority on Error Queue

Normal

2

Which scripts will process the items in the input queue?

Script

script_03_servicesManagement.wal

3

Version

1 - "Script responsible for registering customer in the web"

4

Where will this script run?

Computers

1 Computers

Group (optional)

Group

Delete

5

Previous

Next

#	Description
1	Select “ <i>Normal</i> ” in the Priority on Error Queue field
2	Select “ <i>script_03_servicesManagement</i> ” in the Script field
3	Select the first item (latest version of the script) in the Version field
4	Select the “ <i>Computer_name</i> ” in the Computers field
5	Click on the Next button

5.4.10 Create Process: Variables (1/3)

Create process ×

General

SLA Configuration

Steps

Variables

These variables can be mapped to script variables in order to have their value stored.

4

Add Variable

1

Variable Name (i)

companyCode

2

Type

Numeric

3

Business Key

☒ Yes

Delete

Previous

Create

#	Description
1	Here it is necessary to create the business key with the same name indicated in the code (5.3.5.3 and 5.3.6.3), then write “ <i>companyCode</i> ” in the Variable name field.
2	Select “ <i>Numeric</i> ” in the Type field
3	Set “ <i>Yes</i> ” in the Business Key field
4	Let's include one more variable, which was also defined in the code. Click on the Add Variable button.

5.4.11 Create Process: Variables (2/3)

The screenshot shows the 'Create process' dialog box with the 'Variables' tab selected. The left sidebar has 'General', 'SLA Configuration', 'Steps', and 'Variables' (selected). The main area lists two variables:

- companyCode**: Type is 'Numeric', Business Key is 'Yes' (toggle). A red 'Delete' button is below it.
- companyName**: Variable Name is 'companyName' (annotated with red 1), Type is 'Text' (annotated with red 2), Business Key is 'No' (toggle, annotated with red 3). A red 'Delete' button is below it.

At the bottom right, there are 'Previous' and 'Create' buttons. A red arrow (annotated with red 4) points to the 'Create' button.

The other variables registered in the Bind command (mentioned in previous topics [5.3.5.3](#) and [5.3.6.3](#)) must also be registered. Repeat this step for all variables, filling in the corresponding value:

1 – Variable Name	2 - Type	3 – Business Key	4 – Add Variable
Write “ <i>companyName</i> ”	Select “ <i>Text</i> ”	Set “ <i>No</i> ”	Click on the Add Variable button.
Write “ <i>industry</i> ”	Select “ <i>Text</i> ”	Set “ <i>No</i> ”	Click on the Add Variable button.
Write “ <i>requestedService</i> ”	Select “ <i>Text</i> ”	Set “ <i>No</i> ”	Click on the Add Variable button.
Write “ <i>serviceFeeNumber</i> ”	Select “ <i>Numeric</i> ”	Set “ <i>No</i> ”	Done! Go to the next section

5.4.12 Create Process: Variables (3/3)

Create process ×

General

SLA Configuration

Steps

Variables

These variables can be mapped to script variables in order to have their value stored.

companyCode

companyName

industry

requestedService

serviceFeeNumber

Add Variable +

1

Previous

Create


2

#	Description
1	Check that all variables were added correctly.
4	Click on the Create button to complete the registration.

5.5 Exercise 4: Execute bot and see results.


Now that all the scripts have all the commands, and the entire process registration process has been carried out in the Control Center. Let's run the bot and view the result.

5.5.1 Run Script `getData.WAL`



#	Description
1	Return to IBM RPA Studio, and open the first script, responsible for getting and enqueue data to processing (script_01_getData.wal)
2	Click in Start button to run
3	<p>At this point, it is important to remember that the customer and service registration steps are managed by the IBM RPA Script Orchestrator, that is, as soon as the script_01_getData.wal is executed and inserts an item in the queue, the next steps will automatically be executed.</p> <p>WARNING! Customer registration is done in a java application, so DO NOT USE THE COMPUTER NOW. Wait 10 minutes for the entire process to complete.</p>

5.5.2 See results of the process



#	Description
1	Back in Control Center, let's access the process panel to view processing information. Click on the Workflows menu
2	Select the Control panel tab
3	Select the Processes tab
4	Select the process that created: " <i>Lab3_OrchestratingScripts</i> "
5	This is the main panel for monitoring processing, where: <ul style="list-style-type: none"> • Pending: These are all items that are already in the queue awaiting their turn to be processed. • Processing: It is the number of items being processed (you can have a scenario that allows simultaneous execution). • Done: These are items that have already been successfully processed at all stages of the process, in this case, the customer and service has been successfully registered. • Incomplete: All items that for some reason were not executed successfully.
6	You can see and manage the process steps.

Variables history

Congratulations, you have successfully completed this lab!!!